

D7008FH 8CH FULL D1 H.264 DVR
D7016FH 16CH FULL D1 H.264 DVR

20130824

Feature

- H.264 dual-stream Video compression
- 8/16CH FULL D1**real-timelive view/recording/playback
- Support HDMI, CVBS,VGA output
- Smart video detection: MD, camera blank, video loss
- Alarm triggering screen tips, buzzer, PTZ, e-mail & FTP upload
- Support NTP/DHCP/DDNS/CMS/Web2.0 Browser/P2P
- 4CH Audio Input; 1CH Audio Output
- Support 2 SATA HDD , 2 x USB2.0
- Mobile Phone Surveillance,
- 1U Case



8/16CH	IE	P2P
FULL D1	Safari	CMS
2 SATA	Firefox	DDNS
HDMI	Chrome	Smart Phone

Description

- 8/16CH FULL D1**real-timelive view/recording/playback
- Pentaplex mode: Live view, recording, playback, backup, network and mobile phone surveillance simultaneously
- Support HDMI, CVBS,VGA output simultaneously
- Dual Stream support, Main stream supports encoding at up to D1-real time , sub stream at CIF/QCIF
- Various recording modes: Schedule, manual, motion, sensor
- Various searching modes: Time/calendar, events (alarm, motion)
- Powerful remote surveillance, playback, recording, control, menu setup, recording backupetc.
- Perfect support of iPhone, iPad, Android, etc.
- Multi-user online simultaneously
- Support PTZ control with preset, cruise and track scans
- Support 2 x SATA HDD
- Power DC 12V/4A
- Support multi- languages such as English,French,Russian,Spanish,German etc.

Drawing(rear view)



8channel(video in 1-8) /16channel(video in 1-16)

Specification

MODEL NO.	D7008FH	D7016FH
System	Compression Format	Standard H.264 High Profile
	OS	Embedded Linux
Video	Input	CVBSx 8(BNC) CVBSx 16(BNC)
	Output	BNC x 1 : VGA x 1/ HDMI x 1: 800*600 1024*768 1280*720 1280*1024 1920 x 1080
Audio	Audio Input	RCA x4
	Audio Output	RCA x 1
Recording	Resolution	D1,CIF
	Frame Rate	1~25FPS/PAL,1~30FPS/NTSC
	Bite rate	D1: 384Kbps~2048Kbps CIF: 192Kbps~1024Kbps QCIF: 48Kbps~224Kbps
	Encode	8D1@30fps 16D1@30fps
	Recording Mode	Manual, timer, motion, sensor
Playback	Max Playback Channel	8CH 16CH
	Search Mode	Time, motion, sensor, single or multi-channel
	Fuction	Play, Pause, FF, FB, Digital zoom etc.
Backup	USB Disk	USB2.0 x 2
	Backup Format	DAV,AVI
Remote Application	Dual Stream	Support,CIF/QCIF
	Browser	IE9/10-32bit, Chrome, Firefox,Safari
	Mobile Phone	iPhone, iPad, Android,
Alarm	Alarm Input	8CH 16CH
	Alarm Output	3CH 3CH
Storage	HDD	2 x SATA HDD
PTZ	PTZ	1x RS485
	PTZ Protocol	PELCOP, PELCOD, LILIN, Videon-D, DH-SD1, SHARP, SONY, SAMSUNG, HY etc.
Network	Ethernet	RJ45 100M ethernet
	Protocol	TCP/IP, NTP, UPNP, UDP,DHCP, DNS,PPPOE,DDNS, FTP,E-mail
Others	IR Controller	Yes
	Power Supply	DC: 12V/4A
	Operating Temperature	0 ~50°C
	Humidity	10% ~ 90% Humidity
Mechanical	Chasis Material & Color	Metal & Black
	Product Net weight	2kg
	Product Dimension	360X260X44mm(W x D x H)
Packing	Quantity Box of One Carton	TBD
	Carton Dimension	TBD
	Carton Gross Weight	TBD
Accessories	Power Adapter	1
	Remote controller	1
	Mouse	1
	Screws	8
	CD	1
	Manual	1

■ **Photo List** *Please fill the blanks according to the cameras*

Item	Photo (300x300 resolution)
Carton	
Package	
Product	

Accessories	Qty	Photo(300x300 resolution)
Bracket	NO	
Screw	8	
Screw-driver	NO	
Remote	1	
Connector	2-4	
Power-Adapter	1	
Mouse	1	
CD	1	